

100W LED防水型



- ⊗ 接綫:30cm綫材
- ⊕ L, N: AC輸入
- ⊖ -V黑: DC輸出負端
- ⊕ +V紅: DC輸出正端

輸入電壓範圍 AC input voltage range	170~264VAC 47~63Hz
輸入電流 Input current	1.2A/230V
衝擊電流 AC inrush current	冷啓動電流 60A/230V Cold-start current 60A/230V
漏電電流 Leakage current	<1mA/240VAC
過載保護 Over load protection	105~150% 切斷輸出,自動恢復 105~150% hiccup mode, auto-recovery
防水等級 Water level	IP68
啓動、上升、保持時間 Setup rise hold up time	200ms 50ms 20ms
耐壓性 Withstand voltage	I/P-O/P:1.5KvAC 1 minute I/P-FG:1.5KvAC 1 minute O/P-FG:0.5KvAC 1 minute
工作溫度、濕度 Working temperature	0~40°C@100%put -10°C@80%put 50°C@60%put
重量/包裝 Weight/packing	1. 37kg,20pcs/28kg

型號Type	輸出Output	差值Error	範圍range	效率Efficiency
FS-100-12	12V, 0~8.3A	±1%	100mV	81%
FS-100-15	15V, 0~4.2A	±1%		81%
FS-100-24	24V, 0~2.8A	±1%		84%
FS-100-48	48V, 0~2.1A	±1%		84%