

150W LED防水型



- ⊠ 接綫:30cm綫材
- ⊠ L, N: AC輸入
- ⊠ -V黑: DC輸出負端
- ⊠ +V紅: DC輸出正端

| | |
|---------------------------------------|--|
| 輸入電壓範圍 AC input voltage range | 170~264VAC 47~63Hz |
| 輸入電流 Input current | 1.6A/230V |
| 衝擊電流 AC inrush current | 冷啓動電流 60A/230V Cold-start current 60A/230V |
| 漏電電流 Leakage current | <3.5mA/240VAC |
| 過載保護 Over load protection | 105~150% 切斷輸出,自動恢復 105~150% hiccup mode, auto-recovery |
| 防水等級 Water level | IP68 |
| 啓動、上升、保持時間 Setup rise hold up time | 100ms 50ms 20ms |
| 耐壓性 Withstand voltage | I/P-O/P:1.5KvAC 1 minute I/P-FG:1.5KvAC 1 minute O/P-FG:0.5KvAC 1 minute |
| 工作溫度、濕度 Working temperature | 0~40°C @ 100%put -10°C @ 80%put 50°C @ 60%put |
| 重量/包裝 Weight/packing | 2.8kg,90pcs/26kg |

| 型號Type | 輸出Output | 差值Error | 範圍range | 效率Efficiency |
|-----------|-------------|---------|---------|--------------|
| FS-150-24 | 24V, 0~6.3A | ±1% | 240mV | 85% |
| FS-150-36 | 27V, 0~4.2A | ±1% | 240mV | 86% |
| FS-150-48 | 48V, 0~3.2A | ±1% | 240mV | 87% |